

# **THE CITY OF WEST PEORIA**

## **TABLE OF CONTENTS**

### **TITLE 9: PUBLIC INFRASTRUCTURE**

#### **CHAPTER 1 - NON-SUBDIVISION CURB CUT**

## **TITLE 9      PUBLIC INFRASTRUCTURE**

### **CHAPTER 1 NON-SUBDIVISION CURB CUT**

#### **9-1-1              Curb Repairs**

##### **SECTION 9-1-1              CURB REPAIRS**

The combination concrete curb and sidewalk width shall be 5.5 feet. The curb height above the street grade shall be a minimum of four inches (4") to a maximum of six inches (6"). This height shall be adjusted so that the elevation at the back of the sidewalk shall match the existing yard and so that yard drainage to the street can be maintained. However, the curb height above the street shall never be less than four inches (4"). The face shall have a minimum of eight inches (8") smooth face below grade. The slope of the sidewalk and the apron shall be at two percent (2%) towards the street.

Saw cuts shall be required at the following locations:

- A. In the street, bituminous surface eighteen inches (18") out from the existing curb face to facilitate the removal and replacement of the combination curb and sidewalk.

The eighteen inch (18") wide strip of bituminous surface in front of the existing curb shall be removed. The replaced bituminous surface shall meet the applicable requirements of Section 406 of the IDOT Standard Specifications. The replaced bituminous surface shall match the existing street slope and grade. The proposed pavement should match the existing adjacent construction in material type and thickness.

Inspection required by the Street Department Manager before the concrete is poured.